

INDUSTRIAL PROCESS AND ENERGY OPTIMIZATION

US Army Corp of Engineers

Industry Workshop

GETTYSBURG, PA

FEB 25-27, 2004

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE 26 FEB 2004		2. REPORT TYPE N/A		3. DATES COVERED -	
4. TITLE AND SUBTITLE Energy Savings with a Scalable Source Capture Ventilation				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) PlymoVent Corp				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release, distribution unlimited					
13. SUPPLEMENTARY NOTES See also ADM001865, Industrial Process and Energy Optimization. Proceedings of the Industry Workshop Held in Gettysburg, PA, 25-27 February 2004., The original document contains color images.					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT UU	18. NUMBER OF PAGES 26	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			



Energy Savings with a Scalable Source Capture Ventilation



**BY
Steve Barnkow
PlymoVent Corp**

Why source extraction?

- Significant Energy Savings are realized when capturing the process pollutant at the source vs. using general ventilation methods
- When using general ventilation a high increase in air changes is required at a very high cost
- Protect the operators breathing zone and prevent the contaminant from being spread throughout the building and affecting other people
- 60% savings on Heating and Electric Bills can be achieved when using the source capture method
- 90% savings can be achieved when using source capture combined with “Demand Controlled Ventilation”


Run the process only at the capacity required at any given moment

SOURCE CAPTURE IS COMMONLY USED FOR THE FOLLOWING PROCESSES


- Welding Applications
- Grinding Applications
- Machining Applications
- Vehicle Exhaust Applications

Methods of process ventilation


Natural ventilation




General ventilation with ceiling or wall mounted fans




General ventilation with re-circulation




Source Capture Fume extractors



Source Capture with energy saving controls and a variable speed drive




Source Capture of welding smoke



Source Capture of Grinding Dust



Source Capture of oil mist generated from CNC Lathes



Source Capturing of oil mist with 4' arms---Open machine tools




[Click Here to View Video](#)

Source Capture of Vehicle Exhaust fumes in a maintenance repair facility



Source Capture of Vehicle Exhaust fumes in an Army tank repair facility




Source Capture of vehicle fumes at Dyno Testing Station



[Click Here to View Video](#)

PROCESS VENTILATION WITH HEAT RECOVERY



[Click Here to View Video](#)

TYPICAL CONTROL SENSOR TYPES

- Pressure differential sensor
- Infra-red light sensor
- Inductive electrical sensor
- Particulate sensor
- Relative humidity sensor
- CO sensor
- Hydrogen sensor
- Temp. sensor
- And many others

Energy Saving Analysis

Average temperature on location C	6 degrees C
Ambient air temperature	-15 C
Two shift operation hours	3520h
Year hours	8760h
Energy required to heat 1 m ³ air 1 degree C	0,348W
Min. required efficiency on heat exchanger	50%

	Pcs	Airflow per		Hours /year	Without controls and heat exchanger		With controls and w/o heat exchanger		With controls and heat exchanger	
		point	m3/h		Usage %	Total airflow/h	Usage %	Total airflow/h	Usage %	Total airflow/h
Extraction arms manual welding	5	1 000	3520	100		5 000	30	1 500	30	1 500
Suction tables manual welding	24	1 800	3520	100		43 200	30	12 960	30	12 960
Suction hoods robot welding	8	1 800	3520	100		14 400	80	11 520	80	11 520
General ventilation	1	28 000	8760	100		28 000	100	28 000	100	28 000
Total airflow						90 600		53 980		53 980

Energy consumption per year process ventilation	kWh	1 063 000	445 885	156 153
Energy consumption per year general ventilation	kWh	1 195 000	1 195 000	421 431
Power consumption on fan motor	kWh	497 340	419 724	419 724
Total	kWh	2 755 340	2 060 609	997 308
Savings with control equipment	kWh		694 731	
Savings with control equipment and heat exchanger	kWh			1 758 032

HOW ARE SAVINGS ACHIEVED ?

- **Lower energy consumption** – energy consumption is reduced since the ventilation system only operates when required by the demand of the process.
- **Lower maintenance costs** - maintenance cost will be reduced since the system will not be required to operate at 100% capacity at all times.
- **Lower operating costs** – operating costs will be reduced by more efficient energy saving blower motors which in turn are energy managed by demand controllers.
- **Lower installation costs** – installation costs are reduced by reducing the overall size of the system and its related components such as electrical wiring, motor starters, size of ductwork, and the need for fire suppression.
- **Lower initial purchase costs** – since few manufacturing processes operate at 100% demand, a savings will be achieved by reducing the overall air volume of the system and its filtering systems.

QUESTIONS FROM THE AUDIENCE

THANK YOU FOR YOUR PARTICIPATION.

- If you have any questions or comments, please email them to sbarnkow@plymoventusa.com
- Or Call 732-371-7583